

A scientist in a white lab coat and safety glasses is pouring a clear liquid from a large white jug labeled "Kryo 20" into a metal container. The background shows a laboratory with various equipment and another person working.

LAUDA

HEAT TRANSFER LIQUIDS AND ADDITIVES

°FAHRENHEIT. °CELSIUS. °LAUDA.

INTRODUCTION

LAUDA constant temperature equipment consists of highly precise machines that are optimally designed for temperature control. This includes precise control when approaching the setpoint, maintaining a constant value, and command of change when dynamically moving between setpoints. This precision can only be achieved in conjunction with a heat transfer liquid that harmonizes perfectly with the equipment and is also approved for the required temperature range.

The selection of the correct heat transfer liquid is also crucial for the efficiency of the heat transfer. In this respect, the working temperature range is usually the most important selection criterion. LAUDA heat transfer liquids can be used in a temperature range from -95 to 350 °C. Their heat transfer properties have been tested with LAUDA devices.

Apart from water, the product range includes water-glycol mixtures and polyethylene glycol, as well as mineral and silicone oils.

LAUDA offers optimized heat transfer liquids for both heating and cooling applications.

Heat transfer liquids for temperatures above 0 °C are designated with the name ›Therm‹. Liquids that can also be used below 0 °C bear the name ›Kryo‹. The suffixed number indicates the minimum temperature for ›Kryo‹ and the maximum temperature for ›Therm‹.

OUR 5-YEAR BEST-WARRANTY

Maximum reliability. Comprehensive protection.
Simply register



If you use only LAUDA Heat transfer liquids,
LAUDA offers a **5-Year Best-Warranty**
on registered new devices.

For more information on the specific warranty
terms and conditions, please see page 38 or
www.lauda.de/en/best-warranty



SCAN NOW AND FIND OUT MORE!

Take advantage now

LAUDA PRODUCT LINES

The table below shows the appropriate heat transfer liquids for each product line. Not all heat transfer liquids can be used for all product lines. When selecting a heat transfer liquid, the working temperature, the information in the operating manual and application specific features need to be observed.

Notes

- Never use contaminated heat transfer liquids. Contamination of the pump chamber can lead to blocking of the pump and thus to shutdown of the device.
- Never mix different heat transfer liquids together, even if the substance class or the chemical characterization is identical.
- Always follow the operating manual for the individual product lines to ensure smooth interaction between the heat transfer liquid and the device. Maintenance and fluid change intervals must be complied to guarantee optimum operation with reproducible results.

Product line	 Therm						 Kryo								
	Aqua 90	Therm 160	Therm 180	Therm 250	Ultra 301	Ultra 350	Kryo 10	Kryo 15	Kryo 20	Kryo 30	Kryo 51	Kryo 60	Kryo 65	Kryo 70 A	Kryo 95
Immersion and bath circulation thermostats															
Alpha	●	-	-	-	-	-	●	●	-	●	-	-	-	-	-
Universa ECO	●	-	-	-	-	-	●	●	-	●	-	-	-	-	-
Universa PRO	●	●	●	●	●	-	●	●	●	●	●	●	-	-	●
Universa MAX	●	●	●	●	●	-	●	-	●	●	●	●	-	-	●
Circulation chillers															
Microcool	●	-	-	-	-	-	●	●	-	●	-	-	-	-	-
Ultracool	-	-	-	-	-	-	●	●	-	-	-	-	-	-	-
Circulation and process thermostats															
LOOP	●	-	-	-	-	-	●	●	-	●	-	-	-	-	-
PRO	●	●	●	●	●	-	●	●	●	●	●	●	-	-	●
Variocool	●	-	-	-	-	-	●	●	-	●	-	-	-	-	-
Integral T	●	-	-	-	●	●	●	●	●	●	●	-	-	-	-
Integral XT	-	-	-	-	●	●	-	-	-	●	-	-	●	●	●
Integral P	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-
Ultratemp	-	-	-	-	-	-	●	●	-	-	-	-	-	-	-

● = Approved for product line

● = Limited approval for the product line. Please check the specification

- = Not approved for product line

The following table gives an overview to our LAUDA Heat transfer liquids and water additives with available part numbers depending on volume.

When ordering the heat transfer liquid, please take into account the filling volume of the constant temperature equipment, as well as the volume of the external circuit, if applicable.

Attention: some media have different temperature ranges depending on the device (open or closed systems).

Heat transfer fluid / Chemical substance class	Temperature range for open/half-open systems						Temperature range for closed systems with cold oil overlay						Part Number 5 L / 10 L / 20 L
	-100 °C	-50 °C	0 °C	100 °C	200 °C	300 °C	-100 °C	-50 °C	0 °C	100 °C	200 °C	300 °C	
Aqua 90 Water Page 6			5 °C	90 °C									LZB 120 / 220 / 320
Therm 160 Polyethylene glycol Page 8			60 °C	160 °C									LZB 106 / 206 / 306
Therm 180 Silicone oil Page 10			0 °C	180 °C									LZB 114 / 214 / 314
Therm 250 Silicone oil Page 12			50 °C	250 °C									LZB 122 / 222 / 322
Ultra 301 Mineral oil Page 14			40 °C	230 °C				40 °C				300 °C	LZB 153 / 253 / 353
Ultra 350 Mineral oil Page 16								30 °C				350 °C	LZB 107 / - / -

In open systems the heat transfer liquid is in direct contact with ambient air. Half-open systems are units with a bath opening and a bath cover (e. g. water baths, cooling thermostats).

In closed systems with cold oil overlay the thermally active heat transfer medium does not come into contact with ambient air (e. g. LAUDA Integral XT).

Water additives

LAUDA offers additives for improving performance in combination with water. Refer to the table for the recommended dosage.

Additives:	Usage:	Dose recommendation:	Part Number
Algizide Aquastab Page 36	For the prevention and control of algae formation	5 ml / 10 L Water	LZB 929 (100 ml Btl.) LZB 429 (1 L bottle) LZB 129 (5 L can)
Decalcifier Page 36	Citric acid based decalcifier	100 g / 1 L Water	LZB 126 (5 kg can)

The recommended working temperature range gives you the lowest and the highest temperature for the use of the respective heat transfer medium.

At the lower limit of the temperature range of the heat transfer fluid, a degradation of the temperature control properties is to be expected due to the increasing viscosity. At the upper limit of the heat transfer fluid, increased thermal decomposition is to be expected.

Heat transfer fluid / Chemical substance class	Temperature range for open/half-open systems						Temperature range for closed systems with cold oil overlay						Part Number 5L/10L/20L
	-100°C	-50°C	0°C	100°C	200°C	300°C	-100°C	-50°C	0°C	100°C	200°C	300°C	
Kryo 10 Water/antifreeze Page 18			-10°C		90°C								LZB 132 / 232 / 332 LZB 832 (200 L barrel)
Kryo 15 Water/antifreeze Page 20			-20°C		90°C								LZB 133 / 233 / 333 LZB 833 (200 L barrel)
Kryo 20 Silicone oil Page 22			-20°C		170°C								LZB 116 / 216 / 316
Kryo 30 Water/antifreeze Page 24			-30°C		90°C				-30°C		90°C		LZB 109 / 209 / 309 / LZB 809 (200 L barrel)
Kryo 51 Silicone oil Page 26			-50°C		120°C								LZB 121 / 221 / 321
Kryo 60 Silicone oil Page 28			-60°C		60°C								LZB 102 / 202 / 302 / LZB 802 (200 L barrel)
Kryo 65 Mineral oil Page 30									-65°C		140°C		LZB 118 / 218 / 318 LZB 818 (200 L barrel)
Kryo 70 A Silicone oil Page 32									-70°C		220°C		LZB 131 / 231 / 331 LZB 831 (200 L barrel)
Kryo 95 Silicone oil Page 34			-95°C		60°C				-95°C		160°C		LZB 130 / 230 / 330

In open systems the heat transfer liquid is in direct contact with ambient air. Half-open systems are units with a bath opening and a bath cover (e. g. water baths, cooling thermostats).

In closed systems with cold oil overlay the thermally active heat transfer medium does not come into contact with ambient air (e. g. LAUDA Integral XT).

AQUA 90



Features

- Water-based heat transfer liquid, stabilized against contamination
- Ideal for applications in open temperature control systems for non-flammable liquids

Notes



- Aqua 90 contains no corrosion inhibitors. Materials based on aluminum or galvanized surfaces can therefore be corroded by atmospheric oxygen.
- For our Integral product line, water or Aqua 90 are approved liquids only for models Integral IN 130 T and IN 230 T(W), there is no approval for any other Integral IN device.

Technical Features

Recommended temperature range for open systems	5...90 °C
Chemical characterisation	Aqueous solution of organic, bacteriostatic and fungistatic compounds
Color	Blue, clear
Viscosity, kinematic at 20 °C	1 mm ² /s
Density at 20 °C	998 kg/m ³
Boiling point	100 °C
Water solubility	Completely soluble
Material incompatibility	No known incompatibility with other materials
Part Number 5 L	LZB 120
Part Number 10 L	LZB 220
Part Number 20 L	LZB 320

AQUA 90

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

THERM 160



Features

- Heat transfer liquid for use in baths or open temperature control circuits
- Advantage of cold water solubility in measurement and calibration applications
- Conforms with REACH and RoHs

Notes



- Cannot be used with bath vessels made of polycarbonate.

Technical Features

Recommended temperature range for open systems	60 ... 160 °C
Chemical characterisation	Polyalkylene glycol and additives
Color	Light green - colorless
Viscosity, kinematic at 20 °C	141 mm ² /s
Density at 20 °C	1,034 kg/m ³
Solidifying point	< -36 °C
Flash point	> 260 °C
Boiling point	> 200 °C decomposition
Ignition temperature	> 320 °C
Water solubility	Soluble in cold water
Material incompatibility	Non-ferrous metals, Polycarbonate
Part Number 5 L	LZB 106
Part Number 10 L	LZB 206
Part Number 20 L	LZB 306

THERM 160

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

THERM 180



Features

- Heat transfer liquid for use in baths or open temperature control circuits
- Colorless heat transfer liquid, enables visual control during temperature control
- Chemically inert and environmentally friendly synthetic silicone oil
- Noncorrosive
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for open systems	0 ... 180 °C
Chemical characterisation	Polydimethylsiloxane
Color	Colorless
Viscosity, kinematic at 20 °C	23 mm ² /s
Density at 20 °C	950 kg/m ³
Solidifying point	< -60 °C
Flash point	> 240 °C
Boiling point	≥ 200 °C
Ignition temperature	> 400 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone, Alcohols
Material incompatibility	Silicone
Part Number 5 L	LZB 114
Part Number 10 L	LZB 214
Part Number 20 L	LZB 314

THERM 180

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

THERM 250



Features

- Heat transfer liquid for use in baths or open temperature control circuits
- Thermally stabilized, for use at temperatures above 200 °C
- Chemically inert and environmentally friendly synthetic silicone oil
- Colorless heat transfer liquid, enables visual control during temperature control
- Noncorrosive
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for open systems	50 ... 250 °C
Chemical characterisation	Polymethylphenylsiloxane
Color	Colorless
Viscosity, kinematic at 20 °C	158 mm ² /s
Density at 20 °C	1,065 kg/m ³
Solidifying point	< -50 °C
Flash point	> 300 °C
Boiling point	≥ 260 °C
Ignition temperature	> 400 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone, Alcohols
Material incompatibility	Silicone
Part Number 5 L	LZB 122
Part Number 10 L	LZB 222
Part Number 20 L	LZB 322

THERM 250

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

ULTRA 301



Features

- Heat transfer liquid for temperatures up to over 300 °C
- Silicone-free liquid, ideal for surface-sensitive applications
- The safety data sheet must be observed for uses in bath thermostats

Notes



- Please note the different temperature ranges for open and closed systems.
- We recommend an overlay of nitrogen if using Ultra 301 in open systems.

Technical Features

Recommended temperature range for open systems	40 ... 230 °C
Recommended temperature range for closed systems	40 ... 300 °C
Chemical characterisation	White mineral oil
Color	Colorless
Viscosity, kinematic at 20 °C	76.5 mm ² /s
Density at 20 °C	858 kg/m ³
Solidifying point	-18 °C
Flash point	245 °C
Ignition temperature	330 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone
Material incompatibility	No known incompatibility with other materials
Part Number 5 L	LZB 153
Part Number 10 L	LZB 253
Part Number 20 L	LZB 353

ULTRA 301

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

ULTRA 350



Features

- Heat transfer liquid for temperatures up to over 300 °C
- The liquid is a hazardous substance

Notes



- Use Ultra 350 for the Integral high-temperature thermostats.
- IMPORTANT: EPDM tubing is not allowed to use with Ultra 350.

Technical Features

Recommended temperature range for closed systems	30 ... 350 °C
Chemical characterisation	Dibenzyltoluene
Color	Yellowish clear
Viscosity, kinematic at 20 °C	47 mm ² /s
Density at 20 °C	1,044 kg/m ³
Solidifying point	< -34 °C
Flash point	> 212 °C
Boiling point	390 °C
Ignition temperature	500 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone
Material incompatibility	Perbunan
Part Number 5 L	LZB 107

ULTRA 350

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 10



Features



- Water-glycol mixture for reliable and long-lasting frost and corrosion protection
- Propylene glycol-based heat transfer fluid with high specific heat capacity for open systems
- Suitable for applications in the food and pharmaceutical industries
- The corrosion protection is free from borates, phosphates, nitrites, amines, silicates and CMR substances
- Conforms with REACH and RoHs

Technical Features

Recommended temperature range for open systems	-10 ... 90 °C
Chemical characterisation	Mixture of: water, propylene glycol and corrosion inhibitors
Color	Blue
Viscosity, kinematic at 20 °C	4.3 mm ² /s
Density at 20 °C	1,030 kg/m ³
Water solubility	Completely soluble
Material incompatibility	No known incompatibility with other materials
Part Number 5 L	LZB 132
Part Number 10 L	LZB 232
Part Number 20 L	LZB 332
Part Number 200 L	LZB 832

KRYO 10

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 15



Features

- Water-glycol mixture for reliable and long-lasting frost and corrosion protection
- Ethylene glycol-based heat transfer liquid with high specific heat capacity for open systems
- The corrosion protection is free from borates, phosphates, nitrites, amines, silicates and CMR substances
- Conforms with REACH and RoHs

Notes



- When using Kryo 15 in open systems, the water-glycol mixing ratio may change, with water evaporating at higher temperatures or humidity condensing at lower temperatures. The mixing ratio must therefore be checked according to the application, and the medium replaced, if necessary. If the water content is too high, the constant temperature equipment may be damaged by frost; if the water content is too low, the medium becomes flammable.
- At excessively low temperatures, icing of the evaporator may occur.

Technical Features

Recommended temperature range for open systems	-20 ... 90 °C
Chemical characterisation	Mixture of: water, ethylene glycol, and corrosion inhibitors
Color	Light yellow
Viscosity, kinematic at 20 °C	2.91 mm ² /s
Density at 20 °C	1,051 kg/m ³
Solidifying point	-29 °C
Water solubility	Completely soluble
Material incompatibility	Galvanized components, sealing materials made of polyurethane elastomers (PU), soft PVC and phenol-formaldehyde resins
Part Number 5 L	LZB 133
Part Number 10 L	LZB 233
Part Number 20 L	LZB 333
Part Number 200 L	LZB 833

KRYO 15

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 20



Features

- Heat transfer liquid for use in baths or open temperature control circuits
- Chemically inert and environmentally friendly synthetic silicone oil
- Noncorrosive
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for open systems	-20 ... 170 °C
Chemical characterisation	Polydimethylsiloxane
Color	Colorless
Viscosity, kinematic at 20 °C	11.4 mm ² /s
Density at 20 °C	942 kg/m ³
Solidifying point	< -90 °C
Flash point	> 170 °C
Boiling point	≥ 210 °C
Ignition temperature	> 400 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone, Alcohols
Material incompatibility	Silicone
Part Number 5 L	LZB 116
Part Number 10 L	LZB 216
Part Number 20 L	LZB 316

KRYO 20

Physical properties



Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 30



Features

- Heat transfer liquid with high specific heat capacity for open systems and systems with cold liquid overlay
- Optimized water-glycol mixture for temperatures down to -30°C
- Conforms with REACH and RoHs

Notes



- If Kryo 30 is used in pressurized systems, the lower temperature range is extended to -40°C . The limit increases in the upper temperature range depending on the generated overpressure. Please refer to the operating instructions of your constant temperature equipment for details.
- When using Kryo 30 in open systems, the water-glycol mixing ratio may change, with water evaporating at higher temperatures or humidity condensing at lower temperatures. The mixing ratio must therefore be checked according to the application, and the medium replaced, if necessary. If the water content is too high, the constant temperature equipment may be damaged by frost; if the water content is too low, the medium becomes flammable.
- Do not use Kryo 30 on devices with cascade cooling.

Technical Features

Recommended temperature range for open systems	$-30 \dots 90^{\circ}\text{C}$
Recommended temperature range for closed systems	$-30 \dots 90^{\circ}\text{C}$
Chemical characterisation	A mixture of: water, ethylene glycol and corrosion inhibitors
Color	Light yellow
Viscosity, kinematic at 20°C	$4 \text{ mm}^2/\text{s}$
Density at 20°C	$1,078 \text{ kg/m}^3$
Solidifying point	$< -54^{\circ}\text{C}$
Boiling point	ca. 108°C
Water solubility	Completely soluble
Material incompatibility	Galvanized components, sealing materials made of polyurethane elastomers (PU), soft PVC and phenol-formaldehyde resins
Part Number 5 L	LZB 109
Part Number 10 L	LZB 209
Part Number 20 L	LZB 309
Part Number 200 L	LZB 809

KRYO 30

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 51



Features

- Heat transfer liquid for use in baths or open temperature control circuits
- Chemically inert and environmentally friendly synthetic silicone oil
- Low viscosity, ideal for temperatures below 0 °C
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for open systems	-50 ... 120 °C
Chemical characterisation	Polydimethylphenylsiloxane
Color	Colorless
Viscosity, kinematic at 20 °C	5.6 mm ² /s
Density at 20 °C	924 kg/m ³
Solidifying point	< -100 °C
Flash point	> 120 °C
Boiling point	≥ 200 °C
Ignition temperature	> 320 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone, Alcohols
Material incompatibility	Silicone
Part Number 5 L	LZB 121
Part Number 10 L	LZB 221
Part Number 20 L	LZB 321

KRYO 51

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 60



Features

- Heat transfer liquid for use in baths or open temperature control circuits
- Chemically inert and environmentally friendly synthetic silicone oil
- Low viscosity, ideal for temperatures below 0 °C
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for open systems	-60 ... 60 °C
Chemical characterisation	Polydimethylsiloxane
Color	Colorless
Viscosity, kinematic at 20 °C	3.34 mm ² /s
Density at 20 °C	912 kg/m ³
Solidifying point	< -100 °C
Flash point	> 62 °C
Boiling point	≥ 150 °C
Ignition temperature	> 300 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone, Alcohols
Material incompatibility	Silicone
Part Number 5 L	LZB 102
Part Number 10 L	LZB 202
Part Number 20 L	LZB 302
Part Number 200 L	LZB 802

KRYO 60

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 65



Features

- Heat transfer liquid only for use in systems with cold liquid overlay
- Low viscosity, ideal for temperatures below 0 °C
- Silicone-free liquid, ideal for surface-sensitive applications
- Noncorrosive
- Conforms with REACH and RoHs

Notes



- IMPORTANT: EPDM tubing is not compatible with Kryo 65.

Technical Features

Recommended temperature range for closed systems	-65 ... 140 °C
Chemical characterisation	Mixture of aliphatic hydrocarbons
Color	Colorless
Viscosity, kinematic at 20 °C	1.65 mm ² /s
Density at 20 °C	762 kg/m ³
Solidifying point	< -100 °C
Flash point	62 °C
Boiling point	192 °C
Ignition temperature	247 °C
Water solubility	< 1 mg/L
Solvent	Petrol, Acetone
Material incompatibility	EPDM
Part Number 5 L	LZB 118
Part Number 10 L	LZB 218
Part Number 20 L	LZB 318
Part Number 200 L	LZB 818

KRYO 65

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 70 A



Features

- Heat transfer liquid only for use in systems with cold liquid overlay
- Chemically inert and environmentally friendly synthetic silicone oil
- Low viscosity, ideal for temperatures below 0 °C
- Thermally stabilized, for use at temperatures above 200 °C
- Noncorrosive
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for closed systems	-70 ... 220 °C
Chemical characterisation	Polydimethylsiloxane
Color	Colorless
Viscosity, kinematic at 20 °C	5.3 mm ² /s
Density at 20 °C	924 kg/m ³
Solidifying point	-100 °C
Flash point	125 °C
Boiling point	275 °C
Ignition temperature	355 °C
Water solubility	Insoluble
Solvent	Petrol, Acetone
Material incompatibility	Silicone elastomers
Part Number 5 L	LZB 131
Part Number 10 L	LZB 231
Part Number 20 L	LZB 331
Part Number 200 L	LZB 831

KRYO 70 A

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

KRYO 95



Features

- Heat transfer liquid for use at temperatures below -50°C
- Chemically inert and environmentally friendly synthetic silicone oil
- Low viscosity, ideal for temperatures below 0°C
- Noncorrosive
- Conforms with REACH and RoHs

Notes



- IMPORTANT: silicone tubing is not allowed to use with silicone oils.

Technical Features

Recommended temperature range for open systems	$-95 \dots 60^{\circ}\text{C}$
Recommended temperature range for closed systems	$-95 \dots 160^{\circ}\text{C}$
Chemical characterisation	Polydimethylsiloxane
Color	Colorless
Viscosity, kinematic at 20°C	$1.6 \text{ mm}^2/\text{s}$
Density at 20°C	855 kg/m^3
Solidifying point	$< -111^{\circ}\text{C}$
Flash point	$> 64^{\circ}\text{C}$
Boiling point	190°C
Ignition temperature	$> 325^{\circ}\text{C}$
Water solubility	Insoluble
Solvent	Petrol, Acetone, Alcohols
Material incompatibility	Silicone
Part Number 5 L	LZB 130
Part Number 10 L	LZB 230
Part Number 20 L	LZB 330

KRYO 95

Physical properties



Please pay attention to the safety precautions and hazard statements before use.
The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

WATER ADDITIVES

Please note the dosage.

Falling below the minimum concentration leads to

- lower frost and corrosion protection
- faster bacterial contamination

Exceeding the recommended concentration leads to

- decrease in the frost point
- deterioration of the thermal conduction
- increase in viscosity
- reduction in the thermal capacity of the liquid

ALGICIDE AQUASTAB

Features

- Protective agent for the prevention and control of algae formation in bath thermostats



Technical Features

Recommended temperature range (with water)	5 ... 90 °C
Chemical characterisation	2% Poly(dimethyl imino)-2-hydroxy-1,3-propanediyl chloride
Dose recommendation	5 ml / 10 L Water
Color	Blue, clear
Density at 20 °C	1,050 kg/m ³
Boiling point	100 °C
Water solubility	Completely soluble
Part Number 100 ml	LZB 929
Part Number 1 L	LZB 429
Part Number 5 L	LZB 129

DECALCIFIER

Features

- Citric acid based decalcifier

Notes

- If the temperature unit has lime scale it must be decalcified
- Please empty the temperature unit and add citric acid into the water circuit
- Let stand for 30 minutes (best result with water circulation), then rinse it at least 3 times



Technical Features

Chemical characterisation	Citric acid monohydrate, 2-Hydroxypropane-1,2,3-tri carbonic acid
Dose recommendation	100 g / 1 L Water
Appearance	White granulate
pH value at 25 °C	10 g/L: 2.2; 50 g/L: 1.85
Part Number 5 kg	LZB 126

LAUDA is certified in accordance with the DIN ISO 14001 environmental management system standard. LAUDA is committed to using heat transfer liquids with the lowest possible environmental impact and is constantly working on optimizing its product range according to the latest technologies.

Please pay attention to the safety precautions and hazard statements before use.

The concerning safety data sheet and the product data sheet can be downloaded under www.lauda.de or requested directly from us.

OUR 5-YEAR BEST-WARRANTY

Maximum reliability. Comprehensive protection.
Simply register



SCAN NOW AND FIND OUT MORE!
At www.lauda.de/en/best-warranty

Quick and easy

Activating your 5-Year Best-Warranty

The manufacturer's warranty applies to registered new LAUDA devices and supplements the statutory liability for defects. Our new 5-Year Best-Warranty offers additional security including free repair of material and manufacturing defects. It must be activated with a participating partner within three months of delivery, is non-transferable and expires on resale.



5 years of
peace of mind



Free rectification
of defects



Simple online
registration



Extensive, worldwide
support



Sustainable investment
protection

Three simple steps to register

1. ENTER DEVICE DETAILS

Enter your order number and serial number. The system will instantly verify your device's warranty eligibility.

2. PROVIDE COMPANY INFO

Click »Activate Warranty« and enter your company and contact details.

3. UPLOAD PROOF

Upload a copy of your delivery receipt and proof of your new device and the heat transfer liquid for warranty validation.

YOU'RE ALL SET!

Once registration is complete, you will receive an official warranty confirmation, accessible online at any time.

The following brand names are registered trademarks
of LAUDA DR. R. WOBSE GMBH & CO. KG:
LAUDA Microcool®, LAUDA Universa®, Ultratemp®, Variocool®

LAUDA DR. R. WOBSE GMBH & CO. KG
Laudaplatz 1 • 97922 Lauda-Königshofen • Germany
www.lauda.de

