SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page:

1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| Trade name: | Ultra 350 | |
|-------------------------|---|--|
| REACH registration No.: | 01-2119488667-17-XXXX | |
| | This safety data sheet pertains to the following products: LZB 107: 5 L | |
| | LZB 207: 10 L | |
| | LZB 307: 20 L | |
| CAS-Number: | 53585-53-8 | |
| EC-number: | 258-649-2 | |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| General use: | Heat transfer fluids |
|--------------|-----------------------------------|
| | Industrial use |
| | Professional uses / Public domain |

1.3 Details of the supplier of the safety data sheet

| Company name: | Lauda Dr. R. Wobser GmbH & Co. KG | |
|---|-----------------------------------|--|
| Street/POB-No.: | Laudaplatz 1 | |
| Postal Code, city: | DE-97922 Lauda-Königshofen | |
| WWW: | www.lauda.de | |
| E-mail: | info@lauda.de | |
| Telephone: | +49 (0)9343-503-0 | |
| Telefax: | +49 (0)9343-503-222 | |
| Department responsible for information: | | |

Department Quality Management, Telephone: +49 9343 503-331, e-mail info@lauda.de

1.4 Emergency telephone number

National Poisons Information Service (Birmingham Unit) Telephone: 844 892 0111 Transport: CONSULTANK Lutz Harder GmbH (Contract QUALI003) Telephone: +49 (0)178-4337434 (from USA: 01149 178 4337434)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

| Repr. 1B; H360FD | May damage fertility. May damage the unborn child. | |
|-------------------------|---|-----------------|
| Asp. Tox. 1; H304 | May be fatal if swallowed and enters airways. | |
| Aquatic Chronic 1; H410 |) Very toxic to aquatic life with long lasting effects. | (M-factor = 10) |

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Labelling (CLP)

Signal word:

Material number LZB x07

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page: 2 of 11

2.2 Label elements

| Danger | |
|--------|--|

| - | | |
|---------------------------|---------------|--|
| Hazard statements: | H304 | May be fatal if swallowed and enters airways. |
| | H360FD | May damage fertility. May damage the unborn child. |
| | H410 | Very toxic to aquatic life with long lasting effects. |
| Precautionary statements: | P201 | Obtain special instructions before use. |
| | P273 | Avoid release to the environment. |
| | P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| | P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| | P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| | P331 | Do NOT induce vomiting. |
| | P391 | Collect spillage. |
| Special labelling | | |
| Text for labelling: | Dibenzylbenze | ene, ar-methyl derivative |

2.3 Other hazards

Special danger of slipping by leaking/spilling product. Thermal decomposition: Formation of hydrocarbons.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 3: Composition/information on ingredients

3.1 Substances

| Chemical characterisation: | Dibenzylbenzene, ar-methyl derivative |
|----------------------------|---------------------------------------|
| CAS-Number: | 53585-53-8 |
| EC-number: | 258-649-2 |
| M-factors: | Aquatic Chronic 1: M = 10. |

SECTION 4: First aid measures

4.1 Description of first aid measures

| General information: | If medical advice is needed, have product container or label at hand. First aider: Pay attention to self-protection! Take off contaminated clothing and wash it before reuse. |
|-------------------------|---|
| In case of inhalation: | Move victim to fresh air; if necessary, provide artificial respiration or oxygen. Seek medical attention. |
| Following skin contact: | Remove residues with soap and water. In case of skin reactions, consult a physician. |
| After eye contact: | Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist. |

SAFETY DATA SHEET

Ultra 350 Material number LZB x07

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

| Revision date: | 9/1/2023 |
|----------------|-----------|
| Version: | 10.0 |
| Replaces versi | on: 9.0 |
| Language: | en-GB |
| Date of print: | 20/3/2023 |
| | |

Page:

3 of 11

| After swallowing: | Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious |
|-------------------|--|
| | person. |
| | Caution if victim vomits: Risk of aspiration! Do not induce vomiting. Immediately get medical attention. |

4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, extinguishing powder, carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Combustible. May form dangerous gases and vapours in case of fire. Furthermore, there may develop: aromatic hydrocarbons, carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Additional information: Hazchem-Code: •3Z

Cool endangered containers with water spray and, if possible, remove from danger zone. Do not allow fire water to penetrate into surface or ground water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid exposure. Avoid contact with the substance. If possible, eliminate leakage. Keep unprotected people away. Do not breathe mist/vapours/spray. Ensure adequate ventilation, especially in confined areas. Use respiratory protection whenever ventilation is inadequate. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains. If necessary notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Collect mechanically using liquid-binding material (sand, diatomaceous earth, universal binding agents). Dispose of waste in accordance with local, state, and federal regulations. Final cleaning.

Additional information: Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page: 4 of 11

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advices on safe handling: | Obtain special instructions before use. Do not breathe mist/vapours/spray. Avoid contact with skin. Provide adequate ventilation, and local exhaust as needed. Wear appropriate protective equipment. When using do not eat, drink or smoke. Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Have eye wash bottle or eye rinse ready at work place. | |
|--|--|--|
| Precautions against fire and exp | plosion: | |
| | Take precautionary measures against static discharges. | |
| | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. | |
| 7.2 Conditions for safe storage, including any incompatibilities | | |
| Requirements for storerooms a | ind containers: | |
| | Keep container tightly closed. | |
| | Suitable material for containers/equipment: steel, stainless steel. | |
| Hints on joint storage: | Keep away from food, drink and animal feedingstuffs. | |

int storage: Keep away from food, drink and animal feedingstuffs.Do not store with strong oxidizing agents.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Additional information: | Contains no substances with occupational exposure limit values. |
|-------------------------|--|
| DNEL/DMEL: | DNEL workers, inhalative, long-term, systemic: 0.259 mg/m ³ DNEL workers, dermal, long-term, systemic: 0.37 mg/kg bw/d DNEL consumers, inhalative, long-term, systemic: 64.4 µg/m ³ DNEL consumers, dermal, long-term, systemic: 0.185 mg/kg bw/d DNEL consumers, oral, long-term, systemic: 18.5 µg/kg bw/d |
| PNEC: | PNEC water (freshwater): 0.028 μg/L PNEC water (marine water): 0.003 μg/L PNEC sediment (freshwater): 0.11 mg/kg dw PNEC sediment (marine water): 0.11 mg/kg dw PNEC soil: 2 mg/kg dw PNEC sewage treatment plant: 1,000 mg/L |

8.2 Exposure controls

When vapours form: Withdraw by suction. Provide specialised room ventilation (at least 10 air changes per hour).

Personal protection equipment

Occupational exposure controls

| Respiratory protection: | Respiratory protection in case of aerosol or vapour formation Use filter type A oder A-P2 according to EN 14387. |
|-------------------------|---|
| Hand protection: | Protective gloves according to EN 374. Observe glove manufacturer's instructions concerning penetrability and breakthrough time. |

Document number Q5WA-E_17-016-GB-10, printed by Lauda

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350 Material number LZB x07

| Revision date: | 9/1/2023 |
|----------------|-----------|
| Version: | 10.0 |
| Replaces versi | on: 9.0 |
| Language: | en-GB |
| Date of print: | 20/3/2023 |

Page: 5 of 11

| Eye protection: | Tightly sealed goggles according to EN 166. |
|----------------------------------|--|
| Body protection: | Wear suitable protective clothing. |
| General protection and hygiene n | neasures: |
| | Obtain an airlingto attain the form that Miles and |

Obtain special instructions before use. When using do not eat, drink or smoke. Do not breathe mist/vapours/spray. Avoid contact with skin. Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Appearance: | Physical state at 20 °C and 101.3 kPa: liquid Colour: colourless up to yellow |
|--|---|
| Odour: | weak |
| Odour threshold: | No data available |
| pH: | No data available |
| Melting point/freezing point: | -3932 °C |
| Initial boiling point and boiling range: | approx. 390 °C |
| Flash point/flash point range: | approx. 212 °C |
| Evaporation rate: | No data available |
| Flammability: | No data available |
| Explosion limits: | No data available |
| Vapour pressure: | at 20 °C: <= 0.01 hPa |
| Vapour density: | No data available |
| Density: | >= 1 g/mL |
| Water solubility: | at 20 °C: <= 0.1 mg/L |
| Partition coefficient: n-octanol/water: | at 22 °C: >= 6 log P(o/w) |
| | Based on the n-octanol/water partition coefficient accumulation in organisms is possible. |
| Auto-ignition temperature: | Not self-igniting |
| Decomposition temperature: | Thermal decomposition: Formation of hydrocarbons. |
| Viscosity, kinematic: | at 20 °C: 48 mm²/s at 40 °C: 16 mm²/s |
| Explosive properties: | No data available |
| Oxidizing characteristics: | No data available |
| 9.2 Other information | |

Additional information:

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Refer to subsection "Possilbility of hazardous reactions".

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Heating can release hazardous gases.

10.4 Conditions to avoid

Heat, UV-radiation/sunlight

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition:No hazardous decomposition products when regulations for storage and handling are observed.Thermal decomposition:Thermal decomposition: Formation of hydrocarbons.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

 LD50 Rat, oral:
 > 5000 mg/kg (OECD 401)

 LD50 Rat, dermal:
 > 2000 mg/kg (OECD 402)

 LC0 Rat, inhalative (vapour):
 > 0.24 mg/L/4h (OECD 403)

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page: 6 of 11

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Revision date: 9/1/2023 10.0 Version: Replaces version: 9.0 Language: en-GB Date of print: 20/3/2023

Material number LZB x07 Page: 7 of 11 Acute toxicity (oral): Based on available data, the classification criteria are not met. Toxicological effects Acute toxicity (dermal): Based on available data, the classification criteria are not met. Acute toxicity (inhalative): Based on available data, the classification criteria are not met. Skin corrosion/irritation: Based on available data, the classification criteria are not met. Rabbit: slightly irritant (OECD 404) Serious eye damage/irritation: Based on available data, the classification criteria are not met. Rabbit: Not an irritant (OECD 405) Sensitisation to the respiratory tract: Lack of data. Skin sensitisation: Based on available data, the classification criteria are not met. Guinea pig: not sensitising Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met. In-vitro/in-vivo: negative Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Repr. 1B; H360FD = May damage fertility. May damage the unborn child. Effects on fertility, Rat, oral (OECD 421): NOAEL (P): 250 mg/kg bw/d NOAEL (F1): 250 mg/kg bw/d NOAEL (F2): 80 mg/kg bw/d Developmental toxicity, Rabbit, female, oral (OECD 414): NOAEL (P): 75 mg/kg bw LOAEL developmental toxicity: 10 mg/kg bw Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met. NOAEL Rat, oral: 50 mg/kg (OECD 408) LOAEL Rat, oral: 500 mg/kg (OECD 408) Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met. Rat, oral: NOAEL: 50 mg/kg bw/120 d (OECD 408) Organs affected: liver Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.

General remarks

The substance is metabolized and excreted. Bioaccumulation is unlikely. Absorption exceeding gastrointestinal tract possible.

SECTION 12: Ecological information

12.1 Toxicity

| Aquatic toxicity: | Very toxic to aquatic life with long lasting effects. Fish toxicity: LC50 Danio rerio (zebrafish): 0.00005 mg/L/96h NOEC Leuciscus idus: > 0.46 mg/L/14d |
|-------------------|---|
| | Daphnia toxicity: EC50 Daphnia magna (Big water flea): > 0.029 mg/L/48h NOEC Daphnia magna (Big water flea): 0.0014 mg/L/21d |
| | Algae toxicity: LC50 Skeletonema costatum, growth rate: 0.000016 mg/L/72h |

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page: 8 of 11

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

at 22 °C: >= 6 log P(o/w) Based on the n-octanol/water partition coefficient accumulation in organisms is possible.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Recommendation: Do not empty residuals into drain or WC; send to collection for problem waste. Incinerate according to applicable local, state and federal regulations.

Package

Recommendation: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR: UN 3082

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibenzylbenzene, ar-methyl derivative)

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

14.3 Transport hazard class(es)

ADR/RID: Class 9, Code: M6 IMDG: Class 9, Subrisk -IATA-DGR: Class 9

Ш

yes

14.4 Packing group

ADR/RID:

14.5 Environmental hazards

Marine pollutant:


14.6 Special precautions for user

Land transport (ADR/RID)

| ADP/PID: Kommlor number 00, LIN number LIN 2002 |
|--|
| ADR/RID: Kemmler-number 90, UN number UN 3082 9 |
| 9 274 335 375 601 |
| 5L |
| E1 |
| P001 IBC03 LP01 R001 |
| P001 IBC03 LP01 R001 PP1 |
| |
| MP19 |
| |
| TP1 TP29 |
| LGBV |
| - |
| |
| F-A, S-F |
| 274 335 969 |
| 5 L |
| E1 |
| P001, LP01 |
| PP1 |
| IBC03 |
| - |
| - |
| Τ4 |
| TP2, TP29 |
| Category A. |
| - |
| none |
| |
| Miscellaneous & Environmentally hazardous |
| F1 |
| |
| Pack.Instr. Y964 - Max. Net Qty/Pkg. 30 kg G |
| Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L |
| Pack.Instr. 964 - Max. Net Qty/Pkg. 450 L |
| A97 A158 A197 A215 |
| 9L |
| |

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page: 9 of 11



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code:

•3Z No data available

National regulations - EC member states

EC-number: 258-649-2 Further regulations, limitations and legal requirements: Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Environmental hazards: Code E1, Quantity threshold 100 000 kg / 200 000 kg Use restriction according to REACH annex XVII, no.: 3 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: E1

15.2 Chemical Safety Assessment

No data available

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Ultra 350

Material number LZB x07

Revision date:9/1/2023Version:10.0Replaces version:9.0Language:en-GBDate of print:20/3/2023

Page: 11 of 11

SECTION 16: Other information

Further information

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road Aquatic Chronic: Hazardous to the aquatic environment - chronic AS/NZS: Australian Standards/New Zealand Standards Asp. Tox.: Aspiration toxicity CAS: Chemical Abstracts Service CFR: Code of Federal Regulations CLP: Classification, Labelling and Packaging DMEL: Derived minimal effect level DNEL: Derived no-effect level EC: European Community EC50: Effective Concentration 50% EN: European Standard EQ: Excepted guantities EU: European Union IATA: International Air Transport Association IATA-DGR: Interna@nal Air Transport Associa@n – Dangerous Goods Regula@ns IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IMDG Code: International Maritime Dangerous Goods Code LCO: Lethal concentration 0% LC50: Median lethal concentration LD50: Lethal dose 50% log P(o/w): Partition coefficient: octanol/water MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships M-factor: Multiplication factor NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration OECD: Organisation for Economic Co-operation and Development OSHA: Occupational Safety and Health Administration PBT: Persistent, bioaccumulative and toxic PNEC: Predicted no-effect concentration REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Repr.: Reproductive toxicity RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail TRGS: Technical Rules for Hazardous Substances UN: United Nations UV: Ultraviolet vPvB: Very persistent and very bioaccumulative General revision

Reason of change: Date of first version:

15/10/2012

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.