

Information requirements for high temperature process chillers

Model: UC 80

Type of condensing: Air-cooled

Refrigerant fluid: R410A

Item	Symbol	Value	Unit
Operating temperature	t	7	°C
Seasonal energy performance ratio	SEPR	6,87	[-]
Annual electricity consumption	Q	72249	kWh/a

Parameters at full load and reference ambient temperature at rating point A

Rated refrigeration capacity	P _A	66,97	kW
Rated power input	D _A	22,76	kW
Rated energy efficiency ratio	EER _{DC,A}	2,94	[-]

Parameters at rating point B

Rated refrigeration capacity	P _B	62,51	kW
Rated power input	D _B	14,94	kW
Rated energy efficiency ratio	EER _{DC,B}	4,18	[-]

Parameters at rating point C

Rated refrigeration capacity	P _C	58,04	kW
Rated power input	D _C	9,47	kW
Rated energy efficiency ratio	EER _{DC,C}	6,12	[-]

Parameters at rating point D

Rated refrigeration capacity	P _D	53,58	kW
Rated power input	D _D	5,44	kW
Rated energy efficiency ratio	EER _{DC,D}	9,82	[-]

Other items

Capacity control	Variable		
Degradation co-efficient chillers	C _{dc}	0,90	[-]
GWP of the refrigerant		2088	kg CO ₂ eq (100 years)
Contact details	LAUDA Ultracool S.L. - C/ Colom 606, 08228 Terrassa (Barcelona), España		