

PRODUCT DATA SHEET

Published: 2026-06-29

Pt100 RTD (resistance temperatur detector)

Measuring range: -50 °C ... 180 °C

Part Number: ETP 059-2

Features

- Push-in resistance thermometer with permanently connected silicone cable (length: 31 m), silicone cable shielded
- Connector plug: Lemo connector, size 1, four-pole
- Resistance thermometer (4-wire circuit) class A according to DIN EC 751



Technical Features

Outer diameter

4 mm

Immersion depth

410 mm

Operating temperature range

-50 ... 180 °C

Material

CrNi steel (1.4571)

Length

45 cm

Weight

0.10 kg

Reserve technical changes

LAUDA DR. R. WOBSEY GMBH & CO. KG
Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0
info@lauda.de • www.lauda.de
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim • HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser