

## PRODUCT DATA SHEET

Published: 2026-03-24

LAUDA flow control FC 80 C

LiBus, compatible with Integral IN XT, IN P

Part Number: L004110

### Features

- Flow control system with Coriolis mass flow meter
- User-interface allows setting and control of the temperature control unit
- Allowed heat transfer liquids: Water/glycol mixtures and dielectric fluids such as mineral- or silicone oils
- The maximum controllable volume flow depends on the pump output of the temperature control unit and the pressure drop in the application
- Adjustable pressure limit in application circuit
- Power supply via LAUDA internal Bus-socket of temperature control unit
- With certificate of calibration
- Movable on wheels



### Technical Features

Working temperature range	-40 ... 140 °C
Ambient temperature range	5 ... 40 °C
Flow control range	0.2 ... 70 L/min
Flow measuring range	0.0 ... 99 L/min
Control accuracy flow rate (20 °C; 20 L/min; 1 bar)	0.2 ± L/min
In / Outlet connection thread (outside)	M38 x 1,5
Overall dimensions (WxDxH)	605 x 420 x 740 mm
Weight	62 kg
Power consumption max.	0.02 kW
Power supply	LiBus
Power plug	---

Reserve technical changes

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0  
info@lauda.de • www.lauda.de  
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser