

## PRODUCT DATA SHEET

Published: 2026-09-18

LAUDA Integral IN 1040 XTW Process thermostat  
400 V; 3/PE; 50 Hz & 460 V; 3/PE; 60 Hz  
Part Number: L004121

### Features

- Process thermostat with integrated cooling system for dynamic temperature control within external circuits
- Coloured TFT display for simultaneous indication of actual & set values and graphic illustration of the temperature profile
- Clear text menu navigation, six selectable languages DE, EN, FR, ES, IT, RU
- Management of heat transfer liquids with stored properties
- Easy input via cursor and soft keys. Additional Tmax key for overtemperature protection
- SelfCheck Assistant for system diagnosis
- Emergency stop function via push-button and connection contacts for remote release
- Fully electronic continuous controller with PID action for internal & external control
- Self adapt function for determination of control parameters
- PowerAdapt system for the use of the maximum possible amount of heat permitted by the power supply system
- Low-level and adjustable over-temperature protection with acoustic alarm for use with flammable and non-flammable liquids
- Powerful LAUDA Variopump (pressure pump) with 8 selectable output levels or control of outflow pressure
- USB and Ethernet interface equipped as standard
- Port for external Pt100 integrated, second external Pt100 feasible via interface module
- Remote fault indication through floating contact
- Option for upgrading up to 2 additional interfaces (RS 232/485, Profibus, analogue, contact or EtherCAT module)
- Programmer with 150 temperature/time segments that can be separated into 5 programs
- Integrated web server for browser based operation in local area networks via PC, tablet or smart phone, secure data transfer due to authentication procedure and encryption
- Integrated and adjustable bypass
- Digital display of pump pressure
- Very small internal volume and big non-thermostated expansion vessel (cold fluid layer system)
- Highly efficient SmartCool system for energy-saving digital cooling control with speed-controlled compressor
- Condenser cooling Water



Reserve technical changes

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0  
info@lauda.de • www.lauda.de  
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser

## PRODUCT DATA SHEET

Published: 2026-09-18

LAUDA Integral IN 1040 XTW Process thermostat  
400 V; 3/PE; 50 Hz & 460 V; 3/PE; 60 Hz  
Part Number: L004121

### Features

- Utilizes natural refrigerants CO<sub>2</sub>



Working temperature min.  
-45 °C



Working temperature max.  
220 °C

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0  
info@lauda.de • www.lauda.de  
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser

## PRODUCT DATA SHEET

Published: 2026-09-18

LAUDA Integral IN 1040 XTW Process thermostat  
 400 V; 3/PE; 50 Hz & 460 V; 3/PE; 60 Hz  
 Part Number: L004121

### Technical Features (according to DIN 12876)

|                                               |                                                         |
|-----------------------------------------------|---------------------------------------------------------|
| Working temperature range                     | -45 ... 220 °C                                          |
| Ambient temperature range                     | 5 ... 40 °C                                             |
| Temperature stability                         | 0.05 ± K                                                |
| Heater power max.                             | 8 kW                                                    |
| Power consumption max.                        | 9.9 kW                                                  |
| Current max.                                  | 16 A                                                    |
| Pump Pressure max.                            | 3,1 bar                                                 |
| Pump flow rate max. (pressure)                | 65 L/min                                                |
| In / Outlet connection thread (outside)       | M30 x 1,5                                               |
| Filling volume min.                           | 5.2 L                                                   |
| Filling volume max.                           | 18.2 L                                                  |
| Water cooling connection thread (outside)     | 3/4 "                                                   |
| Recommended cooling water temperature         | 15 °C                                                   |
| Cooling water temperature max.                | 20 °C                                                   |
| Recommended pressure difference cooling water | 3 bar                                                   |
| Pressure difference cooling water min.        | 1 bar                                                   |
| Max. pressure difference cooling water        | 10 bar                                                  |
| Maximum pressure cooling water                | 10 bar                                                  |
| Overall dimensions (WxDxH)                    | 560 x 550 x 1325 mm                                     |
| Weight                                        | 192 kg                                                  |
| Noise level                                   | 66 dB(A)                                                |
| Refrigerant stage 1                           | R-744 (GWP 1); 1.200 kg; 0.0 t CO <sub>2</sub> -eq      |
| Power supply                                  | 400 V; 3/PE; 50 Hz & 460 V; 3/PE; 60 Hz                 |
| Power plug                                    | Power cord with plug (IEC 60309, 5-pol, CEE, red, 16 A) |

Reserve technical changes

LAUDA DR. R. WOBSEY GMBH & CO. KG  
 Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0  
 info@lauda.de • www.lauda.de  
 WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
 Registergericht Mannheim • HRA 560069


Persönlich haftende Gesellschafterin:  
 LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
 Sitz Lauda-Königshofen  
 Registergericht Mannheim • HRB 560226

Geschäftsführer:  
 Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
 Dr. Marc Stricker  
 Beirat: Dr. Gerhard Wobser

## PRODUCT DATA SHEET

Published: 2026-09-18

LAUDA Integral IN 1040 XTW Process thermostat  
400 V; 3/PE; 50 Hz & 460 V; 3/PE; 60 Hz  
Part Number: L004121



Power cord with plug (IEC 60309, 5-pol, CEE, red, 16 A)

| Temperature | Pump stage | Heat transfer liquid | Cooling Capacity 50 Hz | Cooling Capacity 60 Hz |
|-------------|------------|----------------------|------------------------|------------------------|
| 200 °C      | 8          | Thermal oil          | 9.5 kW                 | 9.5 kW                 |
| 100 °C      | 8          | Thermal oil          | 9.5 kW                 | 9.5 kW                 |
| 20 °C       | 8          | Ethanol              | 9.5 kW                 | 9.5 kW                 |
| 10 °C       | 8          | Ethanol              | 9.2 kW                 | 9.2 kW                 |
| 0 °C        | 8          | Ethanol              | 7.3 kW                 | 7.3 kW                 |
| -10 °C      | 8          | Ethanol              | 5.2 kW                 | 5.2 kW                 |
| -20 °C      | 4          | Ethanol              | 4 kW                   | 4 kW                   |
| -30 °C      | 4          | Ethanol              | 2.7 kW                 | 2.7 kW                 |
| -40 °C      | 4          | Ethanol              | 1.6 kW                 | 1.6 kW                 |
| -45 °C      | 2          | Ethanol              | 1.1 kW                 | 1.1 kW                 |

Reserve technical changes

### Standard accessories

- 2 nipples 1/2" with screw cap G3/4 for cooling water

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0  
info@lauda.de • www.lauda.de  
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser


## PRODUCT DATA SHEET

Published: 2026-09-18

LAUDA Integral IN 1040 XTW Process thermostat  
400 V; 3/PE; 50 Hz & 460 V; 3/PE; 60 Hz  
Part Number: L004121

### PUMP CHARACTERISTICS Heat transfer liquid: Water

Pressure bar



- 1 Stage 1
- 2 Stage 2
- 3 Stage 3
- 4 Stage 4
- 5 Stage 5
- 6 Stage 6
- 7 Stage 7
- 8 Stage 8

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Laudaplatz 1 • 97922 Lauda-Königshofen • DE

T + 49 (0) 9343 503-0  
info@lauda.de • www.lauda.de  
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim • HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert,  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser