

# PRODUCT DATA SHEET



## Ultracool UC-0140 SP

Six UC Midi types have cooling outputs ranging from 7.1 up to 26.3 kW. The models work with a reciprocating or scroll compressor and a centrifugal pump. The noise-reduced pump allows customers to easily adjust the water flow. The use of R 134a as refrigerant ensures very low working pressures inside the refrigeration system and operation in ambient temperatures up to 50 °C. The intergrated motor fan speed regulator allows operation in ambient conditions up to -15 °C and reduces the noise level additionally. The models UC-0060 to UC-0240 are also available as UC laser models with pre-configured options included.



Working temperature min.  
-5 °C



Working temperature max.  
25 °C

Technical Attributes	Ultracool UC-0140 SP
Working temperature min.	-5 °C
Working temperature max.	25 °C
Ambient temperature min.	-15 °C
Ambient temperature max.	50 °C
Temperature stability	2 ±K
Cooling output at 25°C water outlet temperature	22.3 kW
Cooling output at 20°C water outlet temperature	20.2 kW
Cooling output at 15°C water outlet temperature	17.1 kW
Cooling output at 10°C water outlet temperature	14 kW
Cooling output at 5°C water outlet temperature	11 kW
Cooling output at 0°C water outlet temperature	8.4 kW
Cooling output at -5°C water outlet temperature	6.3 kW
Number of refrigeration circuits	1
Application	external
Power consumption	5.6 kW

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Pfarrstraße 41/43 · 97922 Lauda-Königshofen  
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222  
info@lauda.de · www.lauda.de  
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim · HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser

## PRODUCT DATA SHEET

### Ultracool UC-0140 SP

Technical Attributes	Ultracool UC-0140 SP
Pump pressure max.	4.2 bar
Pump pressure nominal	3.7 bar
Pump flow max. (pressure)	130 L/min
Pump flow nominal	43.8 L/min
Pump connection thread	HT DN25
Volume water reservoir	100 L
Dimensions (WxDxH) in mm	715x945x1490
Noise level	58.1 dB(A)
Max. fuse	25 A

LAUDA DR. R. WOBSEY GMBH & CO. KG  
 Pfarrstraße 41/43 · 97922 Lauda-Königshofen  
 Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222  
 info@lauda.de · www.lauda.de  
 WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
 Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:  
 LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
 Sitz Lauda-Königshofen  
 Registergericht Mannheim · HRB 560226

Geschäftsführer:  
 Dr. Gunther Wobser (Vors.), Dr. Mario Englert  
 Dr. Marc Stricker  
 Beirat: Dr. Gerhard Wobser