

PRODUCT DATA SHEET

LOOP L 250

The LAUDA LOOP product line includes two thermo-electric circulation thermostats for external temperature control. The temperature control thermostating is by means of a current flow via a semiconductor relay. Both heating and cooling can be achieved simply by reversing polarity in a small space. The two air-cooled device types, L 100 and L 250, provide cooling capacities of 120 and 250 Watts, as well as a temperature range of 4 to 80 °C. The focus is on applications requiring constant temperature with a low power requirement. Both device types are exceptionally efficient in partial-load operation.



Working temperature min.
4 °C



Working temperature max.
80 °C

Technical Attributes

Technical Attributes	LOOP L 250
Working temperature min.	4 °C
Working temperature max.	80 °C
Temperature stability	0.1 ±K
Heater power	0.4 kW
Cooling output at 20 °C	0.25 kW
Power consumption	0.4 kW
Pump pressure max.	0.8 bar
Pump flow max. (pressure)	2.6 L/min
Filling volume max.	0.3 L
Dimensions (WxDxH) in mm	261x368x312

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser