

PRODUCT DATA SHEET

Puridest PD 2 D

With a design life of more than 15 years, LAUDA Puridest stills are one of the most reliable and most robust water treatment systems for laboratories in the world. The perfection of a centuries-old process guarantees high distillate quality on a long-term basis.

Technical Attributes	Puridest PD 2 D
Ambient temperature min.	10 °C
Ambient temperature max.	40 °C
Distillation type	Double
Material	Stainless steel/glass
Production output	2 L/h
Conductivity at 25 °C	2.2 µS/cm
Cooling water flow rate	1.2 L/min
Dimensions (WxDxH) in mm	500x260x470
Weight	21.0 kg
Power consumption	3.5 kW

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 • 97922 Lauda-Königshofen
Postfach 1251 • 97912 Lauda-Königshofen • DE

T +49 (0) 9343 503-0 • F +49 (0) 9343 503-222
info@lauda.de • www.lauda.de
WEEE-Reg-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim • HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim • HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser