

## PRODUCT DATA SHEET



### VS 30 O

The low-noise Varioshake orbital shakers are suitable for the gentle, rapid or vigorous shaking of round vessels such as Erlenmeyer flasks or petri dishes. Depending on the model, they are equipped with user-friendly analog or digital control.

Technical Attributes	VS 30 O
Ambient temperature min.	10 °C
Ambient temperature max.	50 °C
Shaking platform width	676 mm
Shaking platform depth	540 mm
Load capacity max.	30 kg
Shaking amplitude	32 mm
Shaking frequency min.	20 min <sup>-1</sup>
Shaking frequency max.	250 min <sup>-1</sup>
Shaking motion	orbital
Timer	1 minute - 99:59 hours or continuous operation
Dimensions (WxDxH) in mm	705x607x160
Weight	38.0 kg

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Pfarrstraße 41/43 · 97922 Lauda-Königshofen  
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222  
info@lauda.de · www.lauda.de  
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim · HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Mario Englert  
Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser