

PRODUCT DATA SHEET

Versafreeze VF 70040

LAUDA Versafreeze freezers use a high-quality combination of vacuum panels, thermofoil and polyurethane insulation to protect against heating. This enables economical energy consumption, excellent temperature homogeneity and consistency, and short pull-down and maximum warm-up times.



Working temperature min.
-40 °C



Working temperature max.
0 °C

Technical Attributes

Versafreeze VF 70040

Working temperature min.	-40 °C
Working temperature max.	0 °C
Ambient temperature min.	15 °C
Ambient temperature max.	28 °C
Usable volume	731 L
Interior dimensions (WxDxH) in mm	738 x 750 x 1320
Cool down time	from 20 °C to -40 °C in 7 h
Thawing time	from -40 °C to 0 °C in 13 h
Dimensions (WxDxH) in mm	980 x 1165 x 1965

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser