

PRODUCT DATA SHEET

Alpha A Immersion thermostat

The immersion thermostat A can be used for any bath with a wall thickness of up to 30 mm by means of the screw clamp included in the scope of delivery. Using the additional pump circulation set and a cooling coil, the immersion thermostat can be expanded to form a full-fledged thermostating system.



Working temperature min.
25 °C



Working temperature max.
100 °C

Technical Attributes

Working temperature min.

Working temperature max.

Ambient temperature min.

Ambient temperature max.

Temperature stability

Application

Heater power

Power consumption

Dimensions (WxDxH) in mm

Pump pressure max.

Pump flow max. (pressure)

Alpha A Immersion thermostat

25 °C

100 °C

5 °C

40 °C

0.05 ±K

external | External and inside the bath | Inside the bath

1.5 kW

1.5 kW

125x150x300

0.2 bar

15 L/min

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser