

PRODUCT DATA SHEET

ECO RE 415 G

The LAUDA ECO stands out due to its range of functionality and ease of use. A menu navigation in plain text allows easy operation of the devices. Both control heads are equipped with a mini-USB interface as standard. Further interfaces are available as modules. Another innovation is the practical allocation of a flow-rate switch at the front on the control head. This means that individual adjustment of the flow between internal and external circulation is possible even during operation. Variants in 230 V; 50 Hz are also available with natural refrigerants. The most powerful units are equipped with the energy-saving LAUDA SmartCool system. All cooling thermostats are available as air-cooled or water-cooled variants.



Working temperature min.
-15 °C



Working temperature max.
200 °C

Technical Attributes

ECO RE 415 G

| | |
|---|---|
| Working temperature min. | -15 °C |
| Working temperature max. | 200 °C |
| Ambient temperature min. | 5 °C |
| Ambient temperature max. | 40 °C |
| Temperature stability | 0.02 ±K |
| Application | external External and inside the bath Inside the bath |
| Heater power | 2.6 kW |
| Cooling output at 20°C measured with ethanol | 0.18 kW |
| Cooling output at 10°C measured with ethanol | 0.16 kW |
| Cooling output at 0°C measured with ethanol | 0.12 kW |
| Cooling output at -10°C measured with ethanol | 0.08 kW |
| Power consumption | 2.8 kW |
| Interface(s) | Mini-USB |
| Bath volume min. | 3.3 L |
| Bath volume max. | 4 L |

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser

PRODUCT DATA SHEET

ECO RE 415 G

| Technical Attributes | ECO RE 415 G |
|---------------------------|--------------|
| Bath opening width | 130 mm |
| Bath opening depth | 105 mm |
| Bath depth | 160 mm |
| usable depth | 140 mm |
| Pump pressure max. | 0.55 bar |
| Pump flow max. (pressure) | 22 L/min |
| Ø nipples | 13 mm |
| Dimensions (WxDxH) in mm | 180x350x546 |

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser