

## PRODUCT DATA SHEET

### Microcool MC 250

LAUDA Microcool has been designed as a circulation chiller line with five compact models and cooling capacities from 0.25 to 1.2 kW. The user interface with large LED display and the membrane keyboard make the devices easy to use. An RS-232 interface and alarm contact are integrated as standard. What is unusual in this price category of circulation chillers is the high-quality block pump with magnetic coupling. The magnetic coupling of pump and electric motor exclude sealing problems on the pump shaft. LAUDA Microcool circulation chillers are used wherever heat needs to be dissipated reliably and fast, e. g. in laboratories for rotary evaporators, distillation systems or analytical devices.



Working temperature min.  
-10 °C



Working temperature max.  
40 °C

#### Technical Attributes

Technical Attributes	Microcool MC 250
Working temperature min.	-10 °C
Working temperature max.	40 °C
Ambient temperature min.	5 °C
Ambient temperature max.	40 °C
Temperature stability	0.5 ±K
Filling volume min.	2 L
Filling volume max.	4 L
Cooling output at 20°C measured with ethanol	0.25 kW
Cooling output at 10°C measured with ethanol	0.20 kW
Cooling output at 0°C measured with ethanol	0.15 kW
Cooling output at -10°C measured with ethanol	0.09 kW
Power consumption	0.23 kW
Interface(s)	RS-232
Noise level	60 dB(A)
Display resolution	0.1 °C

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Pfarrstraße 41/43 · 97922 Lauda-Königshofen  
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222  
info@lauda.de · www.lauda.de  
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim · HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser

## PRODUCT DATA SHEET

### Microcool MC 250

Technical Attributes	Microcool MC 250
Pump pressure max.	0.35 bar
Pump flow max. (pressure)	16 L/min
Pump connection thread	1/2" (Ø 10)
Dimensions (WxDxH) in mm	200x350x465

LAUDA DR. R. WOBSEY GMBH & CO. KG  
Pfarrstraße 41/43 · 97922 Lauda-Königshofen  
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222  
info@lauda.de · www.lauda.de  
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen  
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:  
LAUDA DR. R. WOBSEY Verwaltungs-GmbH  
Sitz Lauda-Königshofen  
Registergericht Mannheim · HRB 560226

Geschäftsführer:  
Dr. Gunther Wobser (Vors.), Dr. Marc Stricker  
Beirat: Dr. Gerhard Wobser